



Securitron Magnalock Corp.  
Tel 800.624.5625

www.securitron.com  
techsupport@securitron.com

ASSA ABLOY, the global leader  
in door opening solutions

**MODEL: TDK-1 ~ THICK DOOR KIT ~ INSTALLATION INSTRUCTIONS**

**1. INTRODUCTION**

The Securitron TDK-1 Thick Door Kit is designed to allow proper installation of the strike armature for Magnalock Models ~ M32, M38, M62, M68 or M82 series on doors that are greater than 1-7/8 inches in thickness. The TDK-1 thick door kit matrix below will allow you to choose the proper screw length for the thickness of the door your installation requires.

Door Thickness	2"	2-1/4"	2-1/2"	2-3/4"	3"	3-1/4"
Screw Length	2"	2"	2-1/2"	2-1/2"	3"	3"

**2. SPECIFICATIONS**

Use for installations of Magnalock Models M32, M38, M62, M68 or M82 Series. The screws provided meet RoHS Specifications available through Securitron Technical Support.

**3. PRODUCT OVERVIEW**

Upon unpacking this product, an inventory should be made to ensure that all the required hardware has been included. Along with these Instructions this product should include three (3) 5/16-18 flathead hex screws of 2", 2-1/2" and 3" inch in length.

**4. INSTALLATION INSTRUCTIONS**

Securitron TDK-1 thick door kit provides you the proper strike armature screw for the door used in your installation. For proper installation of the strike assembly, refer to the Magnalock Installation Manual.