



2-Port USB KVM Switch Kit

TK-207K (v1.3R)

The 2-Port USB KVM Switch Kit lets you manage two PC's with just one set of keyboard, monitor, and mouse. Switch between two PC's with a simple press of a button! Separate sets of KVM cables are included with the KVM Switch, so users can start controlling 2 PC's instantly. The KVM cables also provide power to the KVM Switch, eliminating the need for a power adapter. Hot Key operations provide immediate access to features such as computer switching, and auto-scanning. With its Hot-Plug, and Audible Feedback, the 2-Port USB KVM Switch is the perfect choice for managing multiple PC's.

PRODUCT OVERVIEW

- 2-port KVM switch with VGA and USB connections to computers
- Device monitoring with Auto-Scan and audible feedback
- High quality 2048 x 1536 resolution for a crisp display
- Support most operating systems and advance mouse designs
- All required cabling included

FEATURES

- Control up to 2 computers / servers with one set of console device
- USB keyboard / mouse emulation with 2 sets of detachable KVM cables
- Compliant with Windows and Linux
- High video quality: up to 2048 x 1536 VGA resolution
- Auto-scan and LED display for computer monitoring
- Keyboard status restored when switching between computers
- Computer selection by front panel push buttons, keyboard hot key commands or Windows-based client switching software*
- User definable hot key (Windows only)
- USB interface power method
- Plug & Play and hot-pluggable
- 2-year limited warranty

* Please go to <http://www.trendnet.com/downloads> to download the client switching software



SPECIFICATIONS

HARDWARE					
Connections	• 2 computers				
USB Interface	• USB 1.1 compliant				
KVM Cable	• 2 sets of 1.2 m (4 ft.) USB KVM cables				
Cable Interface	<table border="1"> <thead> <tr> <th>To KVM</th> <th>To Computer</th> </tr> </thead> <tbody> <tr> <td>• 1 x VGA / SVGA HDB 15-pin (male)</td> <td>• 1 x USB (type A) • 1 x VGA / SVGA HDB 15-Pin (male)</td> </tr> </tbody> </table>	To KVM	To Computer	• 1 x VGA / SVGA HDB 15-pin (male)	• 1 x USB (type A) • 1 x VGA / SVGA HDB 15-Pin (male)
To KVM	To Computer				
• 1 x VGA / SVGA HDB 15-pin (male)	• 1 x USB (type A) • 1 x VGA / SVGA HDB 15-Pin (male)				
PC Port Connectors	• 2 x VGA / SVGA HDB 15-pin (female)				
Console Port Connectors	• 2 x USB Keyboard / Mouse: (type A) • 1 x VGA / SVGA 15-pin HDB (female)				
Computer Selection	• Face panel push buttons, keyboard hot key commands or Windows-based client switching software*				
Supported OS	• Windows and Linux				
Auto-Scan Interval	• 10 seconds				
Keyboard State	• Save and restore				
Power Type	• USB interface power				
Dimensions	• 98 x 70 x 28 mm (3.86 x 2.76 x 1.1 in.)				
Weight	• 99 g (3. 4oz)				
Temperature	• Operating: 0°C ~ 40°C (32°F ~104°F) • Storage: -20°C ~ 60°C (-4°F ~140°F)				
Humidity	• Max 90% (non-condensing)				
Certifications	• CE, FCC				

NETWORKING SOLUTIONS



PACKAGE CONTENTS

TK-207K
Quick Installation Guide
2 sets of USB KVM cables (2 x 1.2 m / 4 ft.)

RELATED PRODUCTS

TK-209K	2-Port USB KVM Switch Kit with Audio
TK-407K	4-Port USB KVM Switch Kit
TK-409K	4-Port USB KVM Switch Kit with Audio

CONTACT INFORMATION

TRENDnet®

20675 Manhattan Place, Torrance, CA 90501 USA
 Tel: 1-310-961-5500
 Fax: 1-310-961-5511
 Web: www.trendnet.com
 Email: sales@trendnet.com
1-888-326-6061

