



2-Port USB KVM Switch Kit with Audio

TK-209K (v1.2R)

The 2-Port USB Audio KVM Switch lets you control multimedia PCs with just one keyboard, monitor, mouse, microphone, and a set of speakers. The KVM switch not only allows you to share your monitor, keyboard and mouse but you can also share microphone and speakers. With just a simple press of a button, this KVM switch eliminates the hassle of cable swapping and switching between 2 PCs. With its Hot-Plug, Auto-Scan and Hot-Key operating features, the TK-209K is the perfect choice for managing 2 PCs. Separate KVM cables are included.

PRODUCT OVERVIEW

- 2-port KVM switch with VGA and USB connections to computers and audio devices
- Listen to music from one computer while working on the other
- High quality 2048 x 1536 resolution for a crisp display
- Supports most operating systems and advance mouse designs
- All required cabling included

FEATURES

- Control up to 2 computers / servers with one set of console device
- USB keyboard / mouse emulation with 2 sets of detachable KVM cables
- Compliant with Windows and Linux
- High video quality, up to 2048 x 1536 VGA resolution
- Listen to music from one computer while working on the other
- Auto-Scan & LED display for computer monitoring
- Computer selection by face panel push buttons, keyboard hot key commands or Windows-based client switching software*
- User definable hot key (Windows only)
- Plug & Play and hot-pluggable
- USB interface power method
- 2-year limited warranty

* Please go to <http://www.trendnet.com/downloads> to download the client switching software




SPECIFICATIONS

HARDWARE

Connections	• 2 computers		
USB Interface	• USB 1.1 compliant		
KVM Cable	• 2 sets of 1.2 m (4 ft.) USB KVM cables • 2 sets of 1.2 m (4 ft.) audio cables (USB mini B to 3.5 mm jack)		
Cable Interface (all male)	KVM Cable	To KVM	To Computer
		• 1 x VGA / SVGA HDB 15-pin	• 1 x USB (type A) • 1 X VGA / SVGA HDB 15-pin
	Audio Cable	• 1 x USB (Mini B)	• 1 x 3.5 mm speaker jack • 1 x 3.5 mm microphone jack
PC Port Connectors (all female)	• 2 x VGA / SVGA HDB 15-pin • 2 x USB (Mini B)		
Console Port Connectors (all female)	• 1 x USB keyboard (type A) • 1 x USB mouse (type A) • 1 x VGA / SVGA HDB 15-pin • 1 x 3.5 mm speaker jack • 1 x 3.5 mm microphone jack		
Supported OS	• Windows and Linux		
Port Selection	• Front panel push buttons, keyboard hot key commands or Windows-based Client Switching software*		
Auto-Scan Interval	• 10 ~ 60 seconds		
Keyboard Status	• Save and restore		
Power Type	• USB Interface Power		
Dimensions	• 98 x 70 x 28 mm (3.86 x 2.76 x 1.1 in.)		
Weight	• 100 g (3.6 oz)		
Temperature	• Operating: 0°C ~ 40°C (32°F ~104°F) • Storage: -20°C ~ 60°C (-4°F ~140°F)		
Humidity	• 0%~90%, non-condensing		
Certifications	• CE, FCC		

2-Port USB KVM Switch Kit with Audio TK-209K



TK-209K

Quick Installation Guide

2 sets of USB KVM cables (1.2 m / 4 ft.)

2 sets of audio cables (1.2 m / 4 ft.)

TK-207K

2-Port USB KVM Switch Kit

TK-208K

2-Port PS/2 KVM Switch Kit with Audio

TK-408K

4-Port PS/2 KVM Switch Kit with Audio

20675 Manhattan Place, Torrance, CA 90501 USA

Tel: 1-310-961-5500

Fax: 1-310-961-5511

Web: www.trendnet.com

Email: sales@trendnet.com

1-888-326-6061

