

MODEL TS-55G

MONITORING/CONTROL STATION



SPECIFICATIONS

- DESIGNED TO RELEASE OR SECURE AND MONITOR ELECTRIC LOCKS
- 1/2" RED LED OPERATES ON 12 OR 24 VOLTS AC OR DC
- 1-1/2" DIA. GREEN ILLUMINATED MOMENTARY PUSHBUTTON WITH HI- BRIGHTNESS BUILT-IN LED
- PUSHBUTTON LED OPERATES ON 12 OR 24 VOLTS AC OR DC
- ONE N/O AND ONE N/C CONTACT RATED 10 AMPS @ 35 VDC OR 120 VAC
- COMPONENTS MOUNTED ON STANDARD SINGLE GANG ELECTRICAL WALLPLATE
- WEATHERPROOF RATED TO IP65, NEMA TYPE 4
- ORDER MODEL TS-56G FOR LATCHING CONTACTS



ALARM CONTROLS CORPORATION

19 BRANDYWINE DRIVE P.O. BOX 280

DEER PARK, NY 11729

1 631 586-4220 1 800 645-5538

WWW.ALARMCONTROLS.COM EMAIL INFO@ALARMCONTROLS.COM

LED WIRING INSTRUCTIONS

FOR 12 VOLT OPERATION

WHITE LEAD POSITIVE

BLACK LEAD NEGATIVE

FOR 24 VOLT OPERATION

RED LEAD POSITIVE

BLACK LEAD NEGATIVE

