

ELECTRONIC DIRECTORY TELEPHONE ACCESS SYSTEMS







TX3-1000-8C Flush Mount Continental Enclosure

Description

Mircom's TX3 Electronic Directory Telephone Access Systems are designed to provide primary resident/ visitor access control for condominiums, apartment buildings, office buildings, gated communities and industrial buildings with up to 2000 residents or users.

Available in a surface Universal enclosure and a flush Continental enclosure, these units come complete with a microphone, tamper resistant speaker and have provisions for a postal lock and color camera to be installed.

The Universal Series enclosure features a built-in rain hood and is constructed of a heavy gauge stainless steel. This unit can be used in a lobby or outdoors and supports surface, semi-flush or pedestal mount applications. The Continental Series enclosure is constructed of a heavy gauge stainless steel and is primarily designed for indoor applications.

These TX3 systems feature a large back-lit 8 line by 20 character electronics LCD display that scrolls a banner message as well as the resident names and dial codes. The enclosures also feature a 16 digit backlit telephone style keypad with dedicated operational buttons for Page Up, Page Down, Call and Info. In addition, the system features a configurable multilingual display and voice prompts with a choice of English, Spanish, or French-Canadian.



TELEPHONE/CARD ACCESS SYSTEMS

Features

- Stainless steel front panel
- Universal Series enclosure is equipped with a built-in rain hood
- Large scrolling 8 x 20 LCD display that eliminates the need for an external directory
- Available in 200, 1000 and 2000 name capacities
- Backit 16 digit keypad with dedicated operational buttons for Page Up, Page Down, Call and Info
- Provisions for postal lock and camera
- Multilingual Display and Voice Greeting (English, French-Canadian and Spanish) that provides instructions on how to use the entry panel
- Concierge/Security Desk/Guard Phone capability
- Card Access Interface
- Supports both AutoDialer (ADC) and NSL (No phone bill)
- Ability to network panels together (peer-to-peer)
- Hands free, full duplex communication
- Flexible one to four digit resident codes
- Dials up to 18 digit telephone numbers
- System can be configured locally using the keypad or a computer with the TX3 configuration software
- Upload/download configuration files without taking the whole system offline
- Programming from one location
- Remote programming with the TX3 configuration software requires a computer equipped with a modem and a TX3-MDM modem module installed in the lobby unit
- Programmable daily usage postal lock
- 5000 record event log
- · Elevator restriction capability
- Industry Canada and F.C.C. approved

Applications

- Provides resident/visitor access control for small buildings such as condominiums, apartment buildings, office buildings, gated communities and industrial buildings
- Designed for applications with up to 2000 residents or users
- Universal enclosure supports surface, semi-flush or pedestal mounting options (Optional adapter plate required to mount to a standard gooseneck post)

CATALOG NUMBER

These systems are programmable via the built-in keypad or using a computer with the optional TX3 configuration software. In addition the systems can also be configured remotely using the TX3 configuration software and the TX3-MDM Modem Module.

The TX3 system utilizes hands-free, full duplex telephone communications between residents and visitors for granting access into the building. The system is configurable to support both an AutoDialer (ADC) system, which uses a dedicated phone line to dial preprogrammed numbers when the unique directory code is entered, and a No Phone Bill (NSL) system, which does not require a dedicated phone line.

The TX3 system comes standard as an ADC system and requires only a dedicated phone line. For NSL configuration the system requires additional hardware components such as relay cards and relay cabinets. (Please refer to the ordering information.)

Dimensions

TX3-200-8U / TX-1000-8U / TX3-2000-8U

16 %"H x 10 1/8"W x 3"D

TX3-UFT Trim Ring

16 ¼"H x 10 %"W x 2 ¾"D (Dimensions are for wall cutout.)

TX3-200-8C / TX-1000-8C / TX3-2000-8C

16 %"H x 10 %"W x 3"D (Dimensions are for wall cutout.) 18 ½"H x 12"W x ½"D (Outside frame dimensions) Continental Enclosures are flush mount only.

Ordering Information

Model	Description	
Surface Universal Series Enclosures (with built-in rain hood)		
TX3-200-8U	Universal Series enclosure c/w 8x20 LCD display, 200 name controller and (1) plug-in transformer	
TX3-1000-8U	Universal Series enclosure c/w 8x20 LCD display, 1000 name controller and (1) plug-in transformer	
TX3-2000-8U	Universal Series enclosure c/w 8x20 LCD display, 2000 name controller and (1) plug-in transformer	
Flush Continental Series Enclosures		
TX3-200-8C	Continental Series enclosure c/w 8x20 LCD display, 200 name controller and (1) plug-in transformer	
TX3-1000-8C	Continental Series enclosure c/w 8x20 LCD display, 1000 name controller and (1) plug-in transformer	
TX3-2000-8C	Continental Series enclosure c/w 8x20 LCD display, 2000 name controller and (1) plug-in transformer	
Universal Series Mounting Accessories		
TX3-UFT	Flush mounting trim kit designed for use with the standard Universal Series enclosures	
TX3-UGA	Gooseneck mounting adapter designed for use with the standard Universal Series enclosures	
No Phone Bill (NSL) Components		
TX3-NSL-8M	Master NSL Relay Cabinet. Supports eight 2012 Telephone Line Relay Cards.	
TX3-8EC	8 Relay Card Expander Cabinet	
TX3-16EC	16 Relay Card Expander Cabinet	
2012	Twelve Unit Telephone Relay Card	
9106	6 ft. relay cable for 2012	
2012K	NSL Relay Card and Cable Kit. Kit includes (1) 2012 twelve unit telephone relay card and (1) 9106 six ft. relay cable	
ADSL-100	ADSL line filter module for NSL applications	
Elevator Restriction Components		
TX3-ER-8	Elevator Restriction Relay Cabinet. Supports eight 2012E Elevator Restriction Relay Cards.	
2012E	Twelve Unit Elevator Restriction Relay Card	
Optional Modules		
CAM-3	Color camera with BNC adaptor cable	
PS-24	24VAC Transformer	
TH-102	Heater Kit. Requires PS-24	
TX3-DATA-MDM	Modem USB 2.0 Stick,one required per PC	
TX3-GPM	Guard Phone Module	
TX3-MDM	Modem Module	
TX3-MSW	TX3 Configuration Software	
TX3-USB-AD	USB to RS485 Adaptor kit includes MD-993 module	



25 Interchange Way Vaughan, Ontario L4K 5W3 Telephone: (905) 660-4655 Fax: (905) 660-4113

4575 Witmer Industrial Estates Niagara Falls, NY 14305 Toll Free: (888) 660-4655 Fax Toll Free: (888) 660-4113

NOT TO BE USED FOR INSTALLATIO	N PURPOSES.
	Distributed by:
/itmer Industrial Estates a Falls, NY 14305	
e: (888) 660-4655 I Free: (888) 660-4113	

