

[TX3] Touch

TOUCH SCREEN TELEPHONE ACCESS SYSTEM



TX3-T-KIOSK
Optional Black Pedestal

Description

Mircom's 22" Touch Surface Mount Telephone Access System is designed to provide a visually stunning and intuitive user-experience.

The system brings a number of innovative new features to provide a fully customizable solution for occupant and visitor access control in condominiums, apartment buildings, office buildings, gated communities and industrial buildings.

The 22" full color touch display provides ultra-wide viewing angles, which is sure to impress visitors & occupants alike.

The solution runs a reliable and proven Windows-based operating system to offer the most feature rich system on the market. For ADC/NSL telephone interconnectivity, the system uses Mircom's custom interface modules, successfully installed in thousands of buildings across the globe

Features

- 22" full color touch display provides ultra-wide viewing angles, sure to impress visitors & occupants alike.
- Call buttons and a scrolling name directory make for an intuitive call interface
- Constructed of heavy gauge 304 stainless steel with a #4 brushed finish for a durable and neutral finish that works perfectly with any décor.
- Interior can conveniently house an optional Card access controller, high definition IP camera, and an optional postal lock are available and can be conveniently housed. Using TIA/EIA-485, multiple panels can be connected for up to 63 nodes, including: card access, voice entry and/or elevator restriction cabinets.
- Allows for easy customization using four fully configurable themes (color & font), 4 preset themes, 4 screen layout templates, as well as a configurable Welcome Screen
- Includes three built-in keyboard layouts (Full QWERTY, Full QWERTY + Num pad, or Simple)
- Standard Wiegand interface for card readers provides a large selection of readers.
- Help button activates a video for easy instructions to the visitor
- An e-mail feature allows visitors to leave private messages for occupants.
- Supports both Auto Dialer (ADC) and No Phone Bill (NSL)
- Elevator restriction capability is available for buildings requiring a higher level of security.
- Variety of programming options available via built-in USB or Ethernet ports, as well as modem and COM-to-RS485 modules to meet your specific site requirements.
- Optional revenue generating advertising module available
- Whisper quiet fan-less operation
- Easily load media content via built-in USB Interface or TCP/IP for advertising or greeting message in JPG, GIF, SWF, WMV and MPEG file formats.
- Industry Canada and F.C.C. approved

Applications


- Provides resident/visitor access control for buildings such as condominiums, apartment buildings, office buildings, gated communities and industrial buildings
- Designed for indoor applications that require a surface mount visitor management system.

CATALOG NUMBER 6546

NOT TO BE USED FOR INSTALLATION PURPOSES.

Mircom reserves the right to make changes at any time without notice in prices, colours, materials, components, equipment, specifications and models and also to discontinue models.

Mechanical Dimensional Diagram



Technical Specifications

Dimensions	45.72 x 81.28 x 10.597 cm (18" x 32" x 4.172")
Weight	31.75 Kg (70 lbs.)
Computer	Intel Atom GENECV05
Hard Drive	High performance CFast card comes standard with 8GB storage
Power	24V DC/156 W – Switching Power Supply included. (RB-MD-990)
Software	Windows 7 Embedded with Microsoft SQL Server Express Database for handling a large number of resident information
Operating Temperature	0-40°C (31°-104°F)
Operating Humidity	90% maximum
Upgrades	IP camera, two door controller, fan, postal lock
Approvals	FCC, Industry Canada

Ordering Information

Model	Description
Surface Mount Touch Screen Telephone Access System	
TX3-TOUCH-S22	Surface Mount Touch Screen Telephone Access System. Includes: Stainless steel enclosure with 22" touch screen LCD display, 8 GB Flash Memory, PC motherboard with Intel Atom processor, 2000 name controller TX3 configuration software and a 24 VDC switching power supply.
TX3-T-KIOSK	Optional Pedestal mount to fasten surface mount unit. Unit base to be bolted to floor.
No Phone Bill (NSL) Components	
TX3-NSL-8M	Master NSL Relay Cabinet. Supports eight 2012 Telephone Line Relay Cards.
TX3-8EC	8 Relay Card Expander Cabinet
TX3-16EC	16 Relay Card Expander Cabinet
2012	Twelve Unit Telephone Relay Card
9106	6 ft. relay cable for 2012
2012K	NSL Relay Card and Cable Kit. Kit includes (1) 2012 twelve unit telephone relay card and (1) 9106 six ft. relay cable
ADSL-100	ADSL line filter module for NSL applications
Elevator Restriction Components	
TX3-ER-8-A	Elevator Restriction Relay Cabinet. Supports eight 2012E Elevator Restriction Relay Cards.
2012E	Twelve Unit Elevator Restriction Relay Card
Card Access Components	
TX3-CX-2K-A	Two Door Access Control System Kit with one TX3-CX Door Controller, two Proximity Readers (SR-2400MI-GR-MP), transformer, TX3-MSW Configuration software and a USB cable. Requires (1) 12V battery 5 Ah to 7 Ah.
CS-MIR-0-0	Clam Shell Proximity Card, must be ordered in groups of 25
KT-MIR-0-0	Key Tag, must be ordered in blocks of 10
TX3-P300-HA	Mullion Mount, Card Reader
TX3-WRR-42	Dual Channel Wiegand Receiver
TX3-WRT-2H	Two Button transmitter with embedded 125 kHz proximity tag, must be ordered in blocks of 10
TX3-WRT-4H	Four Button transmitter with embedded 125 kHz proximity tag, must be ordered in blocks of 10
Optional Modules	
TX3-MDM	Modem Module
TX3-GPM	Guard Phone Module
TX3-MSW	TX3 Configuration Software
TX3-CF-003	Fan
P1204	Axis P1204 Pinhole camera

NOT TO BE USED FOR INSTALLATION PURPOSES.



Mircom™

Canada

25 Interchange Way
Vaughan, Ontario L4K 5W3
Telephone: (905) 660-4655
Fax: (905) 660-4113

U.S.A.

4575 Witmer Industrial Estates
Niagara Falls, NY 14305
Toll Free: (888) 660-4655
Fax Toll Free: (888) 660-4113

Distributed by:

ISO 9001:2008
REGISTERED



CAT. 6546
Rev 1

Web page: <http://www.mircom.com> Email: mail@mircom.com