


IR Indoor/Outdoor Turret Camera

VLEDT1G	2.8-12mm lens, dark grey
VLEDT1W	2.8-12mm lens, white
VLEDT2G	3.6mm lens, dark grey
VLEDT2W	3.6mm lens, white

Features

- 1/3" Panasonic CCD
- 0 lux with 36 IR LEDs built-in (VLEDT1G/VLEDT1W)
- 0 lux with 24 IR LEDs built-in (VLEDT2G/VLEDT2W)
- 98' IR range (depending on scene reflection) (VLEDT1G/VLEDT1W)
- 65' IR range (depending on scene reflection) (VLEDT2G/VLEDT2W)
- IP66 compliant
- 2 year warranty

IR



Specifications

Image Sensor	1/3" Panasonic CCD
Resolution.....	600 TV lines
Minimum Illumination.....	0.1 lux, 0 lux with IR on
Effective Pixels	768 (H) x 494 (V)
Number of IR LEDs	VLEDT1G/VLEDT1W: 36
	VLEDT2G/VLEDT2W: 24
IR Range	VLEDT1G/VLEDT1W:
	Up to 98' (depending on scene reflection)
	VLEDT2G/VLEDT2W:
	Up to 65' (depending on scene reflection)
IR LED Wavelength	850nm
IR Status.....	IR on: under 10 lux, by CDS auto control
Electronic Shutter	Auto (1/60 sec. - 1/100,000 sec.)
S/N Ratio	More than 48dB
Backlight Compensation.....	Auto

White Balance	Auto
AGC.....	Auto Gamma 0.45 typ.
Scanning System.....	2:1 interlace
Synchronization	Internal
Video Signal Output.....	1.0Vp-p / 75 ohms
Operating Temperature.....	14° F – 122° F
Storage Temperature.....	-4° F – 140° F
Power Consumption	Max. 100mA (IR off)
	VLEDT1G/VLEDT1W: max. 400mA (IR on)
	VLEDT2G/VLEDT2W: max. 300mA (IR on)
Power Supply	12VDC (power supply not included)
Dimensions.....	VLEDT1G/VLEDT1W: 4.25" (H) x 4.5" (Dia.)
	VLEDT2G/VLEDT2W: 3.2" (H) x 3.6" (Dia.)
Weight	VLEDT1G/VLEDT1W: 1.2 lbs.
	VLEDT2G/VLEDT2W: 10.4 oz.

Optional Accessory



PSW5
12VDC
Power Supply

Speco Technologies is constantly developing and improving products.
We reserve the right to modify product design and specifications without notice
and without incurring any obligation. Spec Rev. 9/27/13