

WEBS-ZPS – Zone Paging System for Analog WEBS®

Description

Model **WEBS-ZPS** Zone Paging System is a modular telephone zone paging and control system for use with analog WEBS® stations (WEBS-MT/R, WEBS-WM and WEBS-PA-2A).

Features

- One-zone to 99-zones of simultaneous paging
- Up to 32 paging zone groups
- Universal telephone interface designed for direct connection to loop start and ground start trunks, to PBX or KEY paging ports which supply DTMF capability, and to analog Tip/Ring lines
- Modular integration assures reconfiguring and expansion with minimum time and expense
- Field programmable using DTMF and DIP switches
- Emergency All-Call Override Paging



WEBS-ZPS

Specifications

Dimensions (single module):	7.63(194) W x 3.88(99) D x 7.50(191) H in(mm)
Weight (single module):	8.00lbs
Operating Voltage:	12VDC
Operating Current (max):	1.5A
Audio Power Capability:	250W
Operating Temperature:	+25°F to +100°F (-3.9°C to +37.8°C)
Operating Humidity:	0 to 90% non condensing
Mounting:	Mounts to wall or rack with WEBS-RMKT rack mount kit

Options

Zone Paging Module: Model **WEBS-ZPM-9** adds support for an additional 9 paging zones. Up to 10 **WEBS-ZPM-9** modules may be added.