



Models TS-2T, TS-2TD, TS-3T, TS-4T and TS-5T

Electronic Timer Push Buttons

Models

TS-2T

UL 2" Square Green Illuminated Push Button with Timer, SPDT, 2A Continuous Contacts, "PUSH TO EXIT", Single Gang Stainless Steel Wall Plate, 12 or 24 VDC/VAC

TS-2TD

UL 2" Square Green Illuminated Push Button with Timer, DPDT, 2A Continuous Contacts, Dual Timed Output, "PUSH TO EXIT" Single Gang Stainless Steel Wall Plate, 12 or 24 VDC/VAC

TS-3T

UL 2" Square Green Illuminated Push Button with Timer, SPDT, 2A Continuous Contacts, "PUSH TO EXIT", 1/2" Red LED

TS-4T

UL 2" Square Blue Illuminated Push Button with Timer, SPDT, 2A Continuous Contacts, "ADA SYMBOL", 1/2" Red LED

TS-5T

UL 2" Square Blue Illuminated Push Button with Timer, SPDT, 2A Continuous Contacts, "ADA SYMBOL", 1/2" Red LED, Single Gang Stainless Steel Wall Plate, 12 or 24 VDC/VAC

Specifications

- LED illuminated push button 12/24 VDC
- Contacts rated 2A at 35 VDC
- 1/2" red LED operates on 12 or 24 VAC or VDC
- Switch depth behind plate: 2-1/2"

Features

- Switch mounted on single gang wall plate
- Green 2" square push button
- Field connections terminated with colored leads

Options

- 430 stainless steel wallplate
- 2" green square, labeled

"PUSH TO EXIT" with SPDT timed output

- 2" green square, labeled "PUSH TO EXIT" with DPDT timed output
- 2" green square, labeled "PUSH TO EXIT" with 1/2" red LED and SPDT timed output
- 2" blue square, with ADA symbol, with SPDT timed output
- 2" blue square, with ADA symbol, with 1/2" red LED and SPDT timed output
- Adjustable 2 to 45 second SPDT timed contacts
- Adjustable 2 to 45 second DPDT timed contacts

Certifications & Listings

- UL 294 listed

ALARM CONTROLS



ASSA ABLOY

ASSA ABLOY, the global leader in door opening solutions